

# ILLUMINATOR


## TILTING SHOE BASE

### Installation/Wiring Instructions For The Tilting Shoe Base.

**INSTALLATION SHOULD BE PERFORMED BY A QUALIFIED ELECTRICIAN. ALL WIRING MUST COMPLY WITH STATE AND LOCAL CODES.**

1. Install conduit to protect wire from any elements. Allow additional 10" - 12" of wire inside pole for tilting.
2. Secure the four anchor bolts, making sure they are set in the proper position using the provided template.
3. Attach ground wire (green) to eye bolt, and thread into hole on bottom of the Flagpole Beacon™. Tighten jam nut securely against base.
4. Connect wires (black to black, white to white), and insert wire with weighted end into top of flag pole until wire is at pre-measured mark.
5. Attach Beacon to pole.

THE INFORMATION CONTAINED IN THIS DRAWING IS SOLE PROPERTY OF THE FLAG COMPANY, INC. ANY REPRODUCTION IN PART OR IN WHOLE WITHOUT WRITTEN PERMISSION OF THE FLAG COMPANY, INC. IS PROHIBITED.

		<b>THE FLAG COMPANY, INC.</b>	
DRAWN JPW	1-27-04	THE FLAG COMPANY BEACON™	
CHECKED DOW	1-27-04	SIZE A	DWG NUMBER 0000-0000
DESIGNER DOW	1-27-04	REV -	SHEET 1 OF 1
APPROVED Mike L.	1-27-04	SCALE None	

