

Model ECX25

5" - 14 gauge spun aluminum ball
gold anodized

Single sheave truck, cast aluminum
revolving, non-fouling type

2 Bronze swivel snaps with covers
per halyard

1 Set of halyard: #10 poly

1 - 9" Cast aluminum cleat

Aluminum flash collar

3000 PSI concrete

Hardwood wedges
(supplied by others)

Dry sand tightly tamped
after aligning pole

Foundation sleeve -16 ga
hot dip galvanized steel

Steel centering wedges

1/4" Steel base plate

1/4" Steel support plate
welded to grounding spike

Exposed height: 25'-0"

Tapered portion: 11'-0"

Cleat height: 5'-0"

Pole length: 27'-0"

Straight portion: 16'-0"

Foundation: 3'-6"

3'-0"


6"

12"

30"

16"

8"



Truck Detail

Aluminum body
Stainless steel ball bearings
Aluminum sheave
Cast aluminum spindle

All shafts with overall
length of more than
38'-6" are shipped in
two sections.

Each section matched marked
for field assembly. Exposed
portion of jam sleeve must
be **well lubricated** prior to
assembly.

1-1/2" maximum shop
gap allowed for field fitting
(ram for tight joint)



Filename: ECX25 single sheave_revolving truck.ai

Project:	Ground set tapered aluminum flagpole: ALLOY: 6063T6			EDER FLAG	Date:
Location:	Exposed height: 25'-0"	Pole length: 27'-0"		MANUFACTURING COMPANY	Revision:
Architect:	Ship in 1 section	Butt diameter: 5"		1000 W. Rawson Avenue	
Contractor:	Top diameter: 3"	Wall thickness: .125"		Oak Creek, WI 53154	
Customer:	Finish: 100 grit polish				Job: