Titan Series



F Top Diameter				Truck and Ornament (Options Available) See Specification Box	
	A Mounting Height	•		Wire Cable Assembly and Flag Arrangement Assembly (Stainless Steel Wire Aircraft Cable) Two (2) Heavy-Duty Stainless Steel and Two (2) Neoprene Flagsnap Cov Counterweight and Retainer Ring As	Swivel Flagsnaps vers
ų				E Wall Thickness Alloy 6063-T6 Tapered Aluminum To	ube
C Total Length				IWW-GS-10)12
				Flush Access Door with Keyed Lock Continuous Piano Hinge, Manually Winch (Positive Locking At Any Pos and Removable Winch Handle	Operated
				D Butt Diameter	
		4' - 6"		Aluminum Collar (Options Av. See Specification Box Perimeter caulked by Installer	ailable)
	듄			2" Cap - Cement or Waterproof Com and Hardwood Wedges (By Installer)
2	B 12" 6" Set Depth			Ground Sleeve Assembly - 16 Gaug Tamped Dry Sand (By Installer) 3/16" Steel Plate Welded to Sleeve 3/16" Steel Support Plate Lightning Spike - 3/4" Diameter Steel Rod	e Galvanized Steel Tube Note: Foundation design not included. Foundation dimensions should be determined by a qualified Engineer familiar with site soil conditions.

Customer Name:						
Dealer:	Qty: 1					
Project:	Location:					
Notes:						

IWW40D12G-TAG-C2C-ACL

IWW40D12





TRK-9816-GDT Ball Truck - 10" Revolving - Gold



COL1-A10S-ACL FC-11 Spun Alum 1-Piece



ACL Clear Anodized



IWW - WINCH Flush Mount **Hinged Door**

NOTE: Flagpole Components on Anodized and Powder Coat flagpoles (excluding specified Ornaments and Ball Trucks) will match flagpole color specified.

Specifications				
A. Mounting Height: 40'				
B. Set Depth: 4'-0"				
C. Total Length: 44'-0"				
D. Butt Diameter: 10"				
E. Wall Thickness: .188"				
F. Top Diameter: 4"				
Flagpole Sections: 2				
Shaft Weight: 338 lbs.				
Hardware Weight: 32 lbs.				
Ground Sleeve Weight: 63 lbs.				
* Max Flag Size: 8' x 12'				
* Max Wind Speed w/Nylon Flag: 141 mph				
* Max Wind Speed No Flag: 204 mph				
* Wind Speed Specifications from				
ANSI/NAAMM FP 1001-07				

CAFP 010819 1pg